


2024/05/15 0528Z

EGLL GILTI **L179** NIK EDDL

275.51 nm / 510.24 km



## Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

## Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EGLL APT	-	51.47120 -0.46088	0 ft 0 m	-	London Heathrow
GILTI FIX	-	51.57030 2.05505	33,600 ft 10,241 m	94	-
SASKI FIX	L179 AWY-LO	51.54810 2.50000	35,000 ft 10,668 m	16	-
KEGIT FIX	L179 AWY-LO	51.40700 3.10660	30,000 ft 9,144 m	24	-
COA VOR	L179 AWY-LO	51.34810 3.35528	27,900 ft 8,504 m	9	COSTA
HELEN FIX	L179 AWY-LO	51.23530 3.86971	23,500 ft 7,163 m	20	-
NIK VOR	L179 AWY-LO	51.16500 4.18389	20,800 ft 6,340 m	12	NICKY
EDDL APT	-	51.28940 6.76662	0 ft 0 m	97	Dusseldorf

## EGLL

Region: UNITED KINGDOM  
Timezone: EUROPE/LONDON  
Runways: 2

Elevation: 83 ft / 25 m  
Location: 51.471200 -0.460881  
Magnetic Var: 0.379 E

## METAR

EGLL 150520Z AUTO 13005KT 9999 NCD 13/11 Q1003

## TAF

TAF EGLL 142255Z 1500/1606 15007KT 9999 FEW015 PROB40 TEMPO 1500/1507 BKN008 PROB30 1602/1606 6000 BKN005

## Frequencies

REC - 128.07 MHz - HEATHROW INFORMATION	REC - 121.92 MHz - HEATHROW INFORMATION
CLD - 121.97 MHz - HEATHROW DELIVERY	GND - 121.70 MHz - HEATHROW GROUND
GND - 121.85 MHz - HEATHROW GROUND	GND - 121.90 MHz - HEATHROW GROUND
TWR - 118.50 MHz - HEATHROW TOWER	TWR - 118.70 MHz - HEATHROW TOWER
TWR - 124.47 MHz - HEATHROW TOWER	APP - 119.72 MHz - HEATHROW DIRECTOR
APP - 120.40 MHz - HEATHROW DIRECTOR	APP - 134.97 MHz - HEATHROW DIRECTOR
APP - 125.62 MHz - HEATHROW RADAR	APP - 127.52 MHz - HEATHROW RADAR
DEP - 120.52 MHz - HEATHROW DEPARTURE	

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09L	164 ft	12,770 ft	89.66	ASPHALT	1,007 ft	0 ft
	50 m	3,892 m	89.28		307 m	0 m
27R	164 ft	12,770 ft	269.70	ASPHALT	0 ft	177 ft
	50 m	3,892 m	269.33		0 m	54 m
09R	164 ft	11,975 ft	89.68	ASPHALT	1,004 ft	0 ft
	50 m	3,650 m	89.30		306 m	0 m
27L	164 ft	11,975 ft	269.72	ASPHALT	0 ft	95 ft
	50 m	3,650 m	269.34		0 m	29 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	IAA	110.30 MHz	18 nm	-	-	89 ft
				33 km	-		89 m
09R	DME	IBB	109.50 MHz	18 nm	-	-	84 ft
				33 km	-		84 m
27L	DME	ILL	109.50 MHz	18 nm	-	-	84 ft
				33 km	-		84 m
27R	DME	IRR	110.30 MHz	18 nm	-	-	89 ft
				33 km	-		89 m
09L	LOC-ILS	IAA	110.30 MHz	18 nm	89.68	-	83 ft
				33 km	89.30		83 m
09R	LOC-ILS	IBB	109.50 MHz	18 nm	89.70	-	83 ft
				33 km	89.32		83 m
27L	LOC-ILS	ILL	109.50 MHz	18 nm	269.70	-	83 ft
				33 km	269.32		83 m
27R	LOC-ILS	IRR	110.30 MHz	18 nm	269.68	-	83 ft
				33 km	269.30		83 m
09L	GS	IAA	110.30 MHz	10 nm	89.68	3.00	83 ft
				19 km	89.30		83 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09R	GS	IBB	109.50 MHz	10 nm	89.70	3.00	83 ft
				19 km	89.32		83 m
27L	GS	ILL	109.50 MHz	10 nm	269.70	3.00	83 ft
				19 km	269.32		83 m
27R	GS	IRR	110.30 MHz	10 nm	269.68	3.00	83 ft
				19 km	269.30		83 m

## EDDL

Region: GERMANY - CIVIL  
Timezone: EUROPE/BERLIN  
Runways: 2

Elevation: 145 ft / 44 m  
Location: 51.289400 6.766620  
Magnetic Var: 2.679 E

## METAR

EDDL 150520Z AUTO VRB01KT 8000 FEW008 16/14 Q1005 NOSIG

## TAF

TAF EDDL 142300Z 1500/1606 27005KT CAVOK TEMPO 1500/1509 VRB03KT TEMPO 1509/1519 15006KT BECMG 1519/1522 VRB03KT

## Frequencies

REC - 123.77 MHz - ATIS	CLD - 121.77 MHz - CLEARANCE DELIVERY
GND - 121.90 MHz - GROUND	GND - 121.60 MHz - GROUND
GND - 121.67 MHz - GROUND	TWR - 118.30 MHz - TOWER
TWR - 124.35 MHz - TOWER	APP - 128.55 MHz - LANGEN RADAR
APP - 121.35 MHz - LANGEN RADAR	APP - 128.50 MHz - LANGEN RADAR
APP - 128.65 MHz - DUSSELDORF DIRECTOR	DEP - 133.77 MHz - DEPARTURE

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
05R	148 ft	9,851 ft	52.68	CONCRETE	984 ft	659 ft
	45 m	3,003 m	50.00		300 m	201 m
23L	148 ft	9,851 ft	232.71	CONCRETE	984 ft	702 ft
	45 m	3,003 m	230.03		300 m	214 m
05L	148 ft	8,866 ft	52.68	CONCRETE	994 ft	906 ft
	45 m	2,702 m	50.00		303 m	276 m
23R	148 ft	8,866 ft	232.70	CONCRETE	971 ft	928 ft
	45 m	2,702 m	230.02		296 m	283 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
05L	LOC-ILS	IDNE	110.95 MHz	18 nm	52.69	-	145 ft
				33 km	50.01		145 m
05R	LOC-ILS	IDSE	110.15 MHz	18 nm	52.70	-	145 ft
				33 km	50.02		145 m
23L	LOC-ILS	IDSW	109.90 MHz	18 nm	232.70	-	145 ft
				33 km	230.02		145 m
23R	LOC-ILS	IDNW	109.30 MHz	18 nm	232.69	-	145 ft
				33 km	230.01		145 m
05L	GS	IDNE	110.95 MHz	10 nm	52.69	3.00	145 ft
				19 km	50.01		145 m
05R	GS	IDSE	110.15 MHz	10 nm	52.70	3.00	145 ft
				19 km	50.02		145 m
23L	GS	IDSW	109.90 MHz	10 nm	232.70	3.00	145 ft
				19 km	230.02		145 m
23R	GS	IDNW	109.30 MHz	10 nm	232.69	3.00	145 ft
				19 km	230.01		145 m