


2024/06/07 1254Z

KSEA HUH18 CYVR

110.38 nm / 204.42 km



## Notes

Basic altitude profile:

- Ascent Rate: 1200ft/min
- Ascent Speed: 150kts
- Cruise Altitude: 5000ft
- Cruise Speed: 185kts
- Descent Rate: 800ft/min
- Descent Speed: 175kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

## Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KSEA	-	47.45020	0 ft	-	Seattle-Tacoma Intl
APT	-	-122.31200	0 m	-	
HUH18	-	48.84320	5,000 ft	88	Vancouver
FIX	-	-123.00100	1,524 m	-	
CYVR	-	49.19400	0 ft	22	
APT	-	-123.18500	0 m	-	

## KSEA

Region: UNITED STATES  
Timezone: AMERICA/LOS\_ANGELES  
Runways: 3

Elevation: 432 ft / 132 m  
Location: 47.450200 -122.312000  
Magnetic Var: 14.763 E

## METAR

KSEA 071153Z 04006KT 10SM FEW250 12/04 A3007 RMK AO2 SLP187 T01170044 10161 20117 58002

## TAF

TAF KSEA 071120Z 0712/0818 04004KT P6SM FEW250 FM071700 34009KT P6SM FEW250 FM072000 35010G18KT P6SM FEW250 FM0800

## Frequencies

REC - 118.00 MHz - SEATTLE ATIS  
GND - 121.70 MHz - SEATTLE GROUND  
TWR - 120.95 MHz - SEATTLE TOWER  
DEP - 120.10 MHz - SEATTLE DEPARTURE  
CLD - 128.00 MHz - SEATTLE CLEARANCE  
TWR - 119.90 MHz - SEATTLE TOWER  
APP - 133.65 MHz - SEATTLE APPROACH

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16L	151 ft	11,904 ft	180.35	CONCRETE	0 ft	400 ft
	46 m	3,628 m	165.58		0 m	122 m
34R	151 ft	11,904 ft	0.35	CONCRETE	0 ft	400 ft
	46 m	3,628 m	345.58		0 m	122 m
16C	151 ft	9,428 ft	180.34	CONCRETE	0 ft	400 ft
	46 m	2,874 m	165.58		0 m	122 m
34C	151 ft	9,428 ft	0.34	CONCRETE	0 ft	397 ft
	46 m	2,874 m	345.58		0 m	121 m
16R	151 ft	8,502 ft	180.34	CONCRETE	0 ft	200 ft
	46 m	2,591 m	165.58		0 m	61 m
34L	151 ft	8,502 ft	0.34	CONCRETE	0 ft	197 ft
	46 m	2,591 m	345.58		0 m	60 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16C	DME	ISZI	111.70 MHz	18 nm	-	-	470 ft
				33 km	-		470 m
16L	DME	ISNQ	110.30 MHz	18 nm	-	-	369 ft
				33 km	-		369 m
16R	DME	ICJL	110.75 MHz	18 nm	-	-	410 ft
				33 km	-		410 m
34C	DME	ITUC	111.70 MHz	18 nm	-	-	470 ft
				33 km	-		470 m
34L	DME	IBEJ	110.75 MHz	18 nm	-	-	410 ft
				33 km	-		410 m
34R	DME	ISEA	110.30 MHz	18 nm	-	-	469 ft
				33 km	-		469 m
16C	LOC-ILS	ISZI	111.70 MHz	18 nm	180.34	-	355 ft
				33 km	165.57		355 m
16L	LOC-ILS	ISNQ	110.30 MHz	18 nm	180.34	-	338 ft
				33 km	165.58		338 m
16R	LOC-ILS	ICJL	110.75 MHz	18 nm	180.34	-	410 ft
				33 km	165.57		410 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
34C	LOC-ILS	ITUC	111.70 MHz	18 nm	0.34	-	422 ft
				33 km	345.57		422 m
34L	LOC-ILS	IBEJ	110.75 MHz	18 nm	0.34	-	433 ft
				33 km	345.57		433 m
34R	LOC-ILS	ISEA	110.30 MHz	18 nm	0.34	-	428 ft
				33 km	345.58		428 m
16C	GS	ISZI	111.70 MHz	10 nm	180.67	3.00	418 ft
				19 km	165.91		418 m
16L	GS	ISNQ	110.30 MHz	10 nm	180.69	3.00	425 ft
				19 km	165.92		425 m
16R	GS	ICJL	110.75 MHz	10 nm	180.67	3.00	410 ft
				19 km	165.91		410 m
34C	GS	ITUC	111.70 MHz	10 nm	0.67	3.00	367 ft
				19 km	345.91		367 m
34L	GS	IBEJ	110.75 MHz	10 nm	0.67	3.00	360 ft
				19 km	345.91		360 m
34R	GS	ISEA	110.30 MHz	10 nm	0.69	2.75	355 ft
				19 km	345.92		355 m

## CYVR

Region: CANADA

Timezone: AMERICA/VANCOUVER

Runways: 3

Elevation: 13 ft / 4 m

Location: 49.194000 -123.185000

Magnetic Var: 15.256 E

## METAR

CYVR 071200Z 00000KT 20SM SKC 10/08 A3009 RMK SLP192

## TAF

TAF CYVR 071141Z 0712/0818 VRB03KT P6SM SKC BECMG 0714/0716 29012KT BECMG 0808/0810 09005KT FM081600 29008KT P6SM

## Frequencies

REC - 124.60 MHz - ATIS

GND - 121.70 MHz - VANCOUVER GROUND

TWR - 118.70 MHz - VANCOUVER TOWER

APP - 128.60 MHz - VANCOUVER APPROACH

DEP - 126.12 MHz - VANCOUVER DEPARTURE

CLD - 121.40 MHz - CLEARANCE DELIVERY

GND - 127.50 MHz - VANCOUVER GROUND

TWR - 119.55 MHz - VANCOUVER TOWER

APP - 133.10 MHz - VANCOUVER APPROACH

DEP - 132.30 MHz - VANCOUVER DEPARTURE

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08R	200 ft	10,777 ft	99.88	ASPHALT	0 ft	0 ft
	61 m	3,285 m	84.62		0 m	0 m
26L	200 ft	10,777 ft	279.91	ASPHALT	0 ft	0 ft
	61 m	3,285 m	264.65		0 m	0 m
13	200 ft	7,294 ft	141.92	ASPHALT	0 ft	0 ft
	61 m	2,223 m	126.66		0 m	0 m
31	200 ft	7,294 ft	321.93	ASPHALT	0 ft	0 ft
	61 m	2,223 m	306.68		0 m	0 m
08L	200 ft	9,916 ft	99.89	CONCRETE	0 ft	0 ft
	61 m	3,022 m	84.63		0 m	0 m
26R	200 ft	9,916 ft	279.92	CONCRETE	0 ft	0 ft
	61 m	3,022 m	264.66		0 m	0 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08L	DME	ITL	110.55 MHz	18 nm	-	-	1 ft
				33 km	-		1 m
08R	DME	IVR	109.50 MHz	18 nm	-	-	4 ft
				33 km	-		4 m
26L	DME	IFZ	111.95 MHz	20 nm	-	-	10 ft
				37 km	-		10 m
26R	DME	IRD	110.70 MHz	20 nm	-	-	10 ft
				37 km	-		10 m
08L	LOC-ILS	ITL	110.55 MHz	18 nm	99.90	-	13 ft
				33 km	84.64		13 m
08R	LOC-ILS	IVR	109.50 MHz	18 nm	99.89	-	13 ft
				33 km	84.63		13 m
13	LOC-ILS	IMK	111.10 MHz	18 nm	141.93	-	13 ft
				33 km	126.67		13 m
26L	LOC-ILS	IFZ	110.70 MHz	18 nm	279.89	-	13 ft
				33 km	264.63		13 m
26R	LOC-ILS	IRD	111.95 MHz	18 nm	279.90	-	13 ft

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
				33 km	264.64		13 m
08L	GS	ITL	110.55 MHz	10 nm	99.90	3.00	13 ft
				19 km	84.64		13 m
08R	GS	IVR	109.50 MHz	10 nm	99.89	3.00	13 ft
				19 km	84.63		13 m
13	GS	IMK	111.10 MHz	10 nm	141.93	3.00	13 ft
				19 km	126.67		13 m
26L	GS	IFZ	110.70 MHz	10 nm	279.89	3.00	13 ft
				19 km	264.63		13 m
26R	GS	IRD	111.95 MHz	10 nm	279.90	3.00	13 ft
				19 km	264.64		13 m