LFPO
Paris Orly


-

PANC
Ted Stevens Anchorage Intl

2024/03/28 0923Z

LFPO ABSUD **UM733** BIG **UT420** WELIN **UN57** POL **UN601** STN **UN614** OLKER AB **G11** MY **G3** LINDA 6400N01000W KU **J579** MA 6600N01000W 6700N01000W 6800N01000W 6900N01000W 7000N01000W 7100N01000W 7200N01000W 7400N01500W 7500N02000W 7600N02500W 7700N03000W 7800N03500W 7900N04000W 8000N04500W 8000N05000W 8000N05500W 8000N06000W 8000N06500W ROGSO **M453** ADREW **J160** FYU **J120** FAI **V438** SURES PANC

4212.17 nm / 7800.93 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes

- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
LFPO	-	48.72636	0 ft	-	Paris Orly
APT	-	2.36703	0 m		
ABSUD	-	49.93917	26,200 ft	76	-
FIX	-	1.79111	7,986 m		
GUBAR	UM733	50.36028	34,000 ft	35	-
FIX	AWY-HI	1.15056	10,363 m		
GURLU	UM733	50.47778	34,000 ft	9	-
FIX	AWY-HI	0.96861	10,363 m		
BIG	UM733	51.33087	34,000 ft	62	BIGGIN VOR-DME
VOR	AWY-HI	0.03481	10,363 m		
HEMEL	UT420	51.80556	34,000 ft	33	-
FIX	AWY-HI	-0.41944	10,363 m		
BUZAD	UT420	51.94222	34,000 ft	9	-
FIX	AWY-HI	-0.55222	10,363 m		
WELIN	UT420	52.24722	34,000 ft	21	-
FIX	AWY-HI	-0.85222	10,363 m		
TIMPO	UN57	52.55889	34,000 ft	21	-
FIX	AWY-HI	-1.16389	10,363 m		
TNT	UN57	53.05389	34,000 ft	34	TRENT VOR-DME
VOR	AWY-HI	-1.67000	10,363 m		
POL	UN57	53.74389	34,000 ft	44	POLE HILL VOR-DME
VOR	AWY-HI	-2.10333	10,363 m		
RIBEL	UN601	54.01611	34,000 ft	17	-
FIX	AWY-HI	-2.28972	10,363 m		
SHAPP	UN601	54.50000	34,000 ft	31	-
FIX	AWY-HI	-2.62722	10,363 m		
MARGO	UN601	54.70750	34,000 ft	13	-
FIX	AWY-HI	-2.77472	10,363 m		
TLA	UN601	55.49917	34,000 ft	51	TALLA VOR-DME
VOR	AWY-HI	-3.35278	10,363 m		
NEVIS	UN601	56.69528	34,000 ft	82	-
FIX	AWY-HI	-4.54472	10,363 m		
STN	UN601	58.20694	34,000 ft	105	STORNOWAY VOR-DME
VOR	AWY-HI	-6.18306	10,363 m		
OLKER	UN614	61.00000	34,000 ft	168	-
FIX	AWY-HI	-6.50000	10,363 m		
AB	-	61.39528	34,000 ft	24	AKRABERG NDB
NDB	-	-6.68111	10,363 m		
MY	G11	62.10694	34,000 ft	49	MYGGENES NDB
NDB	AWY-HI	-7.58778	10,363 m		
LINDA	G3	62.62167	34,000 ft	73	-
FIX	AWY-HI	-10.00000	10,363 m		
6400N01000W	-	64.00000	35,000 ft	82	-
LATLON	-	-10.00000	10,668 m		
KU	-	64.07000	34,000 ft	5	-
NDB	-	-10.12182	10,363 m		
MA	J579	65.40667	19,500 ft	81	-
NDB	AWY-LO	-9.53681	5,944 m		
6600N01000W	-	66.00000	34,000 ft	37	-
LATLON	-	-10.00000	10,363 m		
6700N01000W	-	67.00000	35,000 ft	60	-
LATLON	-	-10.00000	10,668 m		
6800N01000W	-	68.00000	35,000 ft	60	-

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
LATLON	-	-10.00000	10,668 m		
6900N01000W	-	69.00000	35,000 ft	60	-
LATLON	-	-10.00000	10,668 m		
7000N01000W	-	70.00000	35,000 ft	60	-
LATLON	-	-10.00000	10,668 m		
7100N01000W	-	71.00000	35,000 ft	60	-
LATLON	-	-10.00000	10,668 m		
7200N01000W	-	72.00000	35,000 ft	60	-
LATLON	-	-10.00000	10,668 m		
7400N01500W	-	74.00000	34,000 ft	148	-
LATLON	-	-15.00000	10,363 m		
7500N02000W	-	75.00000	34,000 ft	100	-
LATLON	-	-20.00000	10,363 m		
7600N02500W	-	76.00000	34,000 ft	96	-
LATLON	-	-25.00000	10,363 m		
7700N03000W	-	77.00000	34,000 ft	92	-
LATLON	-	-30.00000	10,363 m		
7800N03500W	-	78.00000	34,000 ft	88	-
LATLON	-	-35.00000	10,363 m		
7900N04000W	-	79.00000	34,000 ft	84	-
LATLON	-	-40.00000	10,363 m		
8000N04500W	-	80.00000	34,000 ft	81	-
LATLON	-	-45.00000	10,363 m		
8000N05000W	-	80.00000	34,000 ft	52	-
LATLON	-	-50.00000	10,363 m		
8000N05500W	-	80.00000	34,000 ft	52	-
LATLON	-	-55.00000	10,363 m		
8000N06000W	-	80.00000	34,000 ft	52	-
LATLON	-	-60.00000	10,363 m		
8000N06500W	-	80.00000	34,000 ft	52	-
LATLON	-	-65.00000	10,363 m		
ROGSO	-	80.18111	34,000 ft	42	-
FIX	-	-69.00000	10,363 m		
ROMDI	M453	80.07028	34,000 ft	215	-
FIX	AWY-HI	-90.00000	10,363 m		
ROKMA	M453	78.56250	34,000 ft	238	-
FIX	AWY-HI	-110.00000	10,363 m		
RODLU	M453	74.38056	34,000 ft	373	-
FIX	AWY-HI	-130.00000	10,363 m		
ADREW	M453	69.16969	34,000 ft	373	-
FIX	AWY-HI	-141.00254	10,363 m		
FYU	J160	66.57427	34,000 ft	183	FORT YUKON VORTAC
DME	AWY-HI	-145.27667	10,363 m		
CHATA	J120	65.22509	34,000 ft	96	-
FIX	AWY-HI	-147.39678	10,363 m		
FAI	J120	64.80008	34,000 ft	29	FAIRBANKS VORTAC
VOR	AWY-HI	-148.01197	10,363 m		
GLOWS	V438	64.43774	18,000 ft	22	-
FIX	AWY-LO	-148.25497	5,486 m		
LIBER	V438	64.04934	18,000 ft	24	-
FIX	AWY-LO	-148.50824	5,486 m		
CAWIN	V438	63.28089	18,000 ft	47	-
FIX	AWY-LO	-148.98821	5,486 m		
SURES	V438	62.27188	14,300 ft	62	-
FIX	AWY-LO	-149.57921	4,359 m		
PANC	-	61.17411	0 ft	66	Ted Stevens Anchorage Intl

Ident	Via	Lat	Alt	Dist	Name
Type		Lon		(nm)	
APT	-	-149.99598	0 m		

LFPO

Region: FRANCE
Timezone: EUROPE/PARIS
Runways: 3

Elevation: 291 ft / 89 m
Location: 48.726300 2.366980
Magnetic Var: 1.434 E

METAR

LFPO 280900Z 21015G27KT 180V260 9999 BKN022 SCT180 08/04 Q0988 TEMPO 21015G30KT 4000 -SHRA

TAF

TAF LFPO 280500Z 2806/2912 19015G25KT 9999 SCT015 SCT040 TEMPO 2806/2817 22015G35KT PROB30 TEMPO 2809/2816 4000 -

Frequencies

REC - 126.50 MHz - ORLY ATIS
CLD - 121.05 MHz - PREFLIGHT
GND - 121.82 MHz - ORLY GROUND
TWR - 120.50 MHz - ORLY TOWER
APP - 123.87 MHz - PARIS APPROACH
DEP - 124.35 MHz - PARIS DEPARTURE
DEP - 128.37 MHz - PARIS DEPARTURE

REC - 131.35 MHz - ORLY ATIS
GND - 121.70 MHz - ORLY GROUND
TWR - 118.70 MHz - ORLY TOWER
APP - 118.85 MHz - PARIS APPROACH
APP - 124.45 MHz - PARIS APPROACH
DEP - 127.75 MHz - PARIS DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
06	148 ft 45 m	11,953 ft 3,643 m	61.78 60.35	ASPHALT	984 ft 300 m	482 ft 147 m
24	148 ft 45 m	11,953 ft 3,643 m	241.82 240.38	ASPHALT	0 ft 0 m	492 ft 150 m
07	148 ft 45 m	10,868 ft 3,313 m	74.34 72.91	CONCRETE	0 ft 0 m	0 ft 0 m
25	148 ft 45 m	10,868 ft 3,313 m	254.38 252.94	CONCRETE	1,427 ft 435 m	0 ft 0 m
02	197 ft 60 m	7,875 ft 2,400 m	18.30 16.87	CONCRETE	0 ft 0 m	492 ft 150 m
20	197 ft 60 m	7,875 ft 2,400 m	198.31 196.88	CONCRETE	0 ft 0 m	492 ft 150 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
06	DME	ORE	108.50 MHz	18 nm 33 km	- -	-	291 ft 291 m
24	DME	OLO	110.90 MHz	18 nm 33 km	- -	-	291 ft 291 m
02	LOC-ILS	OLN	110.30 MHz	18 nm 33 km	18.31 16.88	-	291 ft 291 m
06	LOC-ILS	ORE	108.50 MHz	18 nm 33 km	61.80 60.37	-	291 ft 291 m
07	LOC-ILS	OLE	108.15 MHz	18 nm 33 km	74.36 72.93	-	291 ft 291 m
24	LOC-ILS	OLO	110.90 MHz	18 nm 33 km	241.80 240.37	-	291 ft 291 m
25	LOC-ILS	OLW	111.75 MHz	18 nm 33 km	254.36 252.93	-	291 ft 291 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07	LOC-LOC	OLE	108.15 MHz	18 nm	74.37	-	291 ft
				33 km	72.94		291 m
02	GS	OLN	110.30 MHz	10 nm	18.31	3.00	291 ft
				19 km	16.88		291 m
06	GS	ORE	108.50 MHz	10 nm	61.80	3.00	291 ft
				19 km	60.37		291 m
07	GS	OLE	108.15 MHz	10 nm	74.36	3.00	291 ft
				19 km	72.93		291 m
24	GS	OLO	110.90 MHz	10 nm	241.80	3.00	291 ft
				19 km	240.37		291 m
25	GS	OLW	111.75 MHz	10 nm	254.36	3.00	291 ft
				19 km	252.93		291 m

PANC

Region: USA (ALASKA)
Timezone: AMERICA/ANCHORAGE
Runways: 3

Elevation: 151 ft / 46 m
Location: 61.174300 -149.998000
Magnetic Var: 14.065 E

METAR

PANC 280853Z 00000KT 10SM -RA BKN020 OVC033 02/01 A2983

TAF

PANC 280816Z 2808/2912 21004KT P6SM BKN030 FM281800 18004KT P6SM SCT015 BKN035

Frequencies

REC - 135.50 MHz - D-ATIS
GND - 121.90 MHz - ANCHORAGE GROUND
CLD - 119.40 MHz - CLEARANCE DELIVERY
APP - 118.60 MHz - ANCHORAGE APPROACH
APP - 123.80 MHz - ANCHORAGE APPROACH
DEP - 118.60 MHz - ANCHORAGE DEPARTURE
DEP - 123.80 MHz - ANCHORAGE DEPARTURE

COM - 122.95 MHz - UNICOM
TWR - 118.30 MHz - ANCHORAGE TOWER
CLD - 128.65 MHz - CLEARANCE DELIVERY
APP - 119.10 MHz - ANCHORAGE APPROACH
APP - 126.40 MHz - ANCHORAGE APPROACH
DEP - 119.10 MHz - ANCHORAGE DEPARTURE
DEP - 126.40 MHz - ANCHORAGE DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07R	200 ft 61 m	12,357 ft 3,767 m	89.84 75.78	ASPHALT	0 ft 0 m	0 ft 0 m
25L	200 ft 61 m	12,357 ft 3,767 m	269.90 255.84	ASPHALT	0 ft 0 m	194 ft 59 m
07L	150 ft 46 m	10,566 ft 3,221 m	89.88 75.81	ASPHALT	0 ft 0 m	387 ft 118 m
25R	150 ft 46 m	10,566 ft 3,221 m	269.93 255.86	ASPHALT	0 ft 0 m	387 ft 118 m
15	200 ft 61 m	10,847 ft 3,306 m	164.89 150.82	ASPHALT	0 ft 0 m	397 ft 121 m
33	200 ft 61 m	10,847 ft 3,306 m	344.90 330.84	ASPHALT	463 ft 141 m	236 ft 72 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07L	DME	ITGN	109.90 MHz	18 nm 33 km	- -	-	152 ft 152 m
07R	DME	IANC	111.30 MHz	18 nm 33 km	- -	-	152 ft 152 m
15	DME	IBSC	111.75 MHz	18 nm 33 km	- -	-	152 ft 152 m
07L	LOC-ILS	ITGN	109.90 MHz	18 nm 33 km	89.90 75.83	-	151 ft 151 m
07R	LOC-ILS	IANC	111.30 MHz	18 nm 33 km	89.87 75.80	-	151 ft 151 m
15	LOC-ILS	IBSC	111.75 MHz	18 nm 33 km	164.90 150.83	-	151 ft 151 m
07L	GS	ITGN	109.90 MHz	10 nm 19 km	89.90 75.83	3.00	151 ft 151 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07R	GS	IANC	111.30 MHz	10 nm 19 km	89.87 75.80	3.00	151 ft 151 m
15	GS	IBSC	111.75 MHz	10 nm 19 km	164.90 150.83	3.00	151 ft 151 m