


2024/05/05 1913Z

YSSY RIVET **Y59** EBONY LIZZI MAITE MONTY EGEKA SHEED YMML

390.91 nm / 723.97 km



Notes

Requested: YSSY RIVET Y59 EBONY LIZZI MAITE MONTY EGEKA SHEED YMML

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
YSSY	-	-33.94927	0 ft	-	Sydney Intl
APT	-	151.18135	0 m	-	
RIVET	-	-34.28083	0 ft	42	-
FIX	-	150.43028	0 m	-	-
TARAL	Y59	-34.50194	0 ft	27	-
FIX	AWY-LO	149.93361	0 m	-	-
CULIN	Y59	-34.74000	0 ft	30	-
FIX	AWY-LO	149.39000	0 m	-	-
NONUP	Y59	-35.43056	0 ft	67	-
FIX	AWY-LO	148.29889	0 m	-	-
ARRAN	Y59	-35.83750	0 ft	40	-
FIX	AWY-LO	147.63944	0 m	-	-
EBONY	Y59	-36.18250	0 ft	34	-
FIX	AWY-LO	147.07056	0 m	-	-
LIZZI	-	-37.45056	0 ft	102	-
FIX	-	145.63806	0 m	-	-
MAITE	-	-37.64722	0 ft	21	-
FIX	-	145.26194	0 m	-	-
MONTY	-	-37.72528	0 ft	8	-
FIX	-	145.11194	0 m	-	-
EGEKA	-	-37.72789	0 ft	4	-
FIX	-	145.01964	0 m	-	-
SHEED	-	-37.73083	0 ft	4	-
FIX	-	144.91472	0 m	-	-
YMML	-	-37.66530	0 ft	5	Melbourne Intl
APT	-	144.83667	0 m	-	

YSSY

Region: AUSTRALIA
Timezone: AUSTRALIA/SYDNEY
Runways: 3

Elevation: 21 ft / 6 m
Location: -33.946100 151.177000
Magnetic Var: 12.671 E

METAR

YSSY 051900Z AUTO 16020KT 9999 // SCT029 18/14 Q1024 RF00.0/028.0

TAF

TAF AMD YSSY 051700Z 0518/0700 15020G30KT 9999 -SHRA SCT020 FM060800 15014KT 9999 -SHRA SCT030 INTER 0518/0608 VR

Frequencies

REC - 118.55 MHz - ATIS	REC - 126.55 MHz - ATIS
TWR - 124.70 MHz - SYDNEY TOWER	TWR - 120.50 MHz - SYDNEY TOWER
GND - 126.50 MHz - SYDNEY GROUND	GND - 121.70 MHz - SYDNEY GROUND
GND - 130.95 MHz - ANSETT APRON	GND - 127.60 MHz - SYDNEY COORDINATOR
CLD - 133.80 MHz - SYDNEY CLEARANCE DELIVERY	APP - 124.40 MHz - SYDNEY APPROACH
APP - 128.30 MHz - SYDNEY APPROACH	APP - 135.90 MHz - SYDNEY APPROACH
APP - 126.10 MHz - SYDNEY DIRECT	APP - 125.30 MHz - SYDNEY DIRECT
APP - 133.95 MHz - ILS MONITOR	APP - 119.45 MHz - ILS MONITOR
DEP - 129.70 MHz - SYDNEY DEPARTURE	DEP - 128.30 MHz - SYDNEY DEPARTURE
DEP - 123.00 MHz - SYDNEY DEPARTURE	DEP - 118.40 MHz - SYDNEY DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
16L	148 ft	8,018 ft	167.85	ASPHALT	758 ft	295 ft
	45 m	2,444 m	155.18		231 m	90 m
34R	148 ft	8,018 ft	347.85	ASPHALT	125 ft	295 ft
	45 m	2,444 m	335.18		38 m	90 m
07	148 ft	8,285 ft	74.14	ASPHALT	0 ft	489 ft
	45 m	2,525 m	61.46		0 m	149 m
25	148 ft	8,285 ft	254.12	ASPHALT	331 ft	197 ft
	45 m	2,525 m	241.45		101 m	60 m
16R	148 ft	13,029 ft	167.86	ASPHALT	279 ft	299 ft
	45 m	3,971 m	155.19		85 m	91 m
34L	148 ft	13,029 ft	347.85	ASPHALT	0 ft	620 ft
	45 m	3,971 m	335.18		0 m	189 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
07	DME	ISY	109.90 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
16L	DME	ISS	110.90 MHz	18 nm	-	-	30 ft
				33 km	-		30 m
25	DME	ISW	109.70 MHz	18 nm	-	-	33 ft
				33 km	-		33 m
34R	DME	IKN	109.30 MHz	18 nm	-	-	20 ft
				33 km	-		20 m
07	LOC-ILS	ISY	109.90 MHz	18 nm	74.13	-	21 ft
				33 km	61.46		21 m
16L	LOC-ILS	ISS	110.90 MHz	18 nm	167.85	-	21 ft
				33 km	155.18		21 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16R	LOC-ILS	IKS	109.50 MHz	18 nm	167.86	-	21 ft
				33 km	155.19		21 m
25	LOC-ILS	ISW	109.70 MHz	18 nm	254.13	-	21 ft
				33 km	241.46		21 m
34L	LOC-ILS	ISN	110.10 MHz	18 nm	347.86	-	21 ft
				33 km	335.19		21 m
34R	LOC-ILS	IKN	109.30 MHz	18 nm	347.85	-	21 ft
				33 km	335.18		21 m
07	GS	ISY	109.90 MHz	10 nm	74.13	3.00	21 ft
				19 km	61.46		21 m
16L	GS	ISS	110.90 MHz	10 nm	167.85	3.00	21 ft
				19 km	155.18		21 m
16R	GS	IKS	109.50 MHz	10 nm	167.86	3.00	21 ft
				19 km	155.19		21 m
25	GS	ISW	109.70 MHz	10 nm	254.13	3.00	21 ft
				19 km	241.46		21 m
34L	GS	ISN	110.10 MHz	10 nm	347.86	3.00	21 ft
				19 km	335.19		21 m
34R	GS	IKN	109.30 MHz	10 nm	347.85	3.00	21 ft
				19 km	335.18		21 m

YMML

Region: AUSTRALIA
Timezone: AUSTRALIA/MELBOURNE
Runways: 2

Elevation: 433 ft / 132 m
Location: -37.665500 144.837000
Magnetic Var: 11.562 E

METAR

YMML 051903Z 27006KT 1500 BCFG BKN003 09/09 Q1031 RF00/0/000/2

TAF

TAF AMD YMML 051824Z 0518/0700 25006KT 9999 SCT005 FM052100 18008KT 9999 SCT005 BECMG 0600/0602 18010KT 9999 SCT005

Frequencies

REC - 132.67 MHz - YMML ATIS
GND - 121.70 MHz - MELBOURNE GND
APP - 132.00 MHz - MELBOURNE APP

CLD - 127.20 MHz - MELBOURNE INTL CLD
TWR - 120.50 MHz - MELBOURNE TWR
DEP - 118.90 MHz - MELBOURNE DEP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
09	148 ft	7,513 ft	94.00	ASPHALT	0 ft	197 ft
	45 m	2,290 m	82.44		0 m	60 m
27	148 ft	7,513 ft	273.98	ASPHALT	0 ft	174 ft
	45 m	2,290 m	262.42		0 m	53 m
16	155 ft	12,012 ft	171.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	160.04		0 m	61 m
34	155 ft	12,012 ft	351.60	ASPHALT	0 ft	200 ft
	47 m	3,661 m	340.04		0 m	61 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	LOC-ILS	IMS	109.70 MHz	18 nm	171.60	-	433 ft
				33 km	160.04		433 m
27	LOC-ILS	IMW	109.30 MHz	18 nm	273.99	-	433 ft
				33 km	262.43		433 m
16	GS	IMS	109.70 MHz	10 nm	171.60	3.00	433 ft
				19 km	160.04		433 m
27	GS	IMW	109.30 MHz	10 nm	273.99	3.00	433 ft
				19 km	262.43		433 m