

EIDW

Dublin


EGSS

Stansted

2024/05/13 1137Z

EIDW DOLOP Y124 AMPIT L15 KEPAD L151 TELBA EGSS

261.05 nm / 483.47 km



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: no

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
EIDW	-	53.42490	0 ft	-	Dublin
APT	-	-6.26308	0 m		
DOLOP	-	53.21420	34,000 ft	95	-
FIX	-	-3.63083	10,363 m		
AMPIT	Y124	53.19420	32,100 ft	15	-
FIX	AWY-LO	-3.19250	9,784 m		
RISLA	L15	53.03080	28,900 ft	14	-
FIX	AWY-LO	-2.88667	8,809 m		
KEPAD	L15	52.80970	24,700 ft	19	-
FIX	AWY-LO	-2.47889	7,529 m		
TELBA	L151	52.66440	22,400 ft	10	-
FIX	AWY-LO	-2.31861	6,828 m		
EGSS	-	51.88510	0 ft	104	Stansted
APT	-	0.23499	0 m		

EIDW

Region: IRELAND
Timezone: EUROPE/DUBLIN
Runways: 2

Elevation: 240 ft / 73 m
Location: 53.424900 -6.263080
Magnetic Var: 1.974 W

METAR

EIDW 131100Z 11015KT 3000 -RADZ SCT004 BKN006 11/10 Q0999 TEMPO 6000 BKN010

TAF

TAF AMD EIDW 130733Z 1307/1406 13013KT 7000 -RA SCT005 BKN010 TEMPO 1307/1319 3000 -RADZ BKN005 TEMPO 1307/1315 1300 -RA

Frequencies

REC - 124.52 MHz - ATIS	TWR - 118.60 MHz - DUBLIN TOWER
GND - 118.75 MHz - DUBLIN GROUND	GND - 121.80 MHz - DUBLIN GROUND
CLD - 121.87 MHz - CLEARANCE DELIVERY	APP - 133.27 MHz - DUBLIN APPROACH
APP - 121.10 MHz - DUBLIN APPROACH	APP - 119.92 MHz - DUBLIN APPROACH
APP - 119.55 MHz - DUBLIN APPROACH	REC - 118.50 MHz - DUBLIN INFORMATION

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10R	148 ft	8,660 ft	95.26	ASPHALT	0 ft	0 ft
	45 m	2,640 m	97.23		0 m	0 m
28L	148 ft	8,660 ft	275.29	ASPHALT	0 ft	0 ft
	45 m	2,640 m	277.26		0 m	0 m
16	190 ft	6,805 ft	156.64	ASPHALT	0 ft	0 ft
	58 m	2,074 m	158.61		0 m	0 m
34	190 ft	6,805 ft	336.65	ASPHALT	0 ft	0 ft
	58 m	2,074 m	338.62		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
16	DME	IAC	111.50 MHz	18 nm	-	-	200 ft
				33 km	-		200 m
10R	LOC-ILS	IDE	108.90 MHz	18 nm	95.26	-	242 ft
				33 km	97.23		242 m
16	LOC-ILS	IAC	111.50 MHz	18 nm	156.64	-	242 ft
				33 km	158.61		242 m
28L	LOC-ILS	IDW	111.35 MHz	18 nm	275.26	-	242 ft
				33 km	277.23		242 m
10R	GS	IDE	108.90 MHz	10 nm	95.26	3.00	242 ft
				19 km	97.23		242 m
16	GS	IAC	111.50 MHz	10 nm	156.64	3.00	242 ft
				19 km	158.61		242 m
28L	GS	IDW	111.35 MHz	10 nm	275.26	3.00	242 ft
				19 km	277.23		242 m

EGSS

Region: UNITED KINGDOM
Timezone: EUROPE/LONDON
Runways: 1

Elevation: 348 ft / 106 m
Location: 51.885100 0.234989
Magnetic Var: 0.579 E

METAR

EGSS 131120Z AUTO 19012KT 9999 SCT020 OVC026 18/12 Q1008

TAF

TAF EGSS 130505Z 1306/1412 18010KT 8000 BKN008 BECMG 1306/1309 9999 SCT025 BECMG 1319/1322 11005KT BECMG 1323/1400 18010KT 9999 SCT020 OVC026 18/12 Q1008

Frequencies

DEP - 120.62 MHz - ESSEX RADAR	APP - 120.62 MHz - ESSEX RADAR
APP - 132.05 MHz - STANSTED APPROACH	CLD - 121.95 MHz - STANSTED CLEARANCE DELIVERY
GND - 121.72 MHz - STANSTED GROUND	TWR - 123.80 MHz - STANSTED TOWER
TWR - 125.55 MHz - STANSTED TOWER	APP - 136.20 MHz - STANSTED DIRECT
REC - 114.55 MHz - ATIS	REC - 127.17 MHz - ATIS

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04	151 ft	9,984 ft	42.78	ASPHALT	974 ft	0 ft
	46 m	3,043 m	42.21		297 m	0 m
22	151 ft	9,984 ft	222.81	ASPHALT	0 ft	0 ft
	46 m	3,043 m	222.23		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04	DME	ISED	110.50 MHz	18 nm	-	-	348 ft
				33 km	-		348 m
22	DME	ISX	110.50 MHz	18 nm	-	-	348 ft
				33 km	-		348 m
04	LOC-ILS	ISED	110.50 MHz	18 nm	42.80	-	348 ft
				33 km	42.22		348 m
22	LOC-ILS	ISX	110.50 MHz	18 nm	222.80	-	348 ft
				33 km	222.22		348 m
04	GS	ISED	110.50 MHz	10 nm	42.80	3.00	348 ft
				19 km	42.22		348 m
22	GS	ISX	110.50 MHz	10 nm	222.80	3.00	348 ft
				19 km	222.22		348 m