KAVP

Wilkes Barre Scranton Intl


KORD

Chicago Ohare Intl

2024/03/19 0407Z

KAVP +41.27_-075.78 +41.23_-075.84 +41.22_-075.92 +41.22_-075.99 +41.46_-078.49 +41.65_-080.00 +41.78_-083.52 +41.88_-087.62 +41.87_-087.70 +41.88_-087.77 +41.91_-087.84 KORD

553.15 nm / 1024.43 km



Notes

Departing runway 21 KAVP. Arriving runway 14 KORD.

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KAVP APT	–	41.32870 -75.73153	0 ft 0 m	–	–
+41.27_-075.78 LATLON	–	41.26773 -75.78341	520 ft 158 m	4	–
+41.23_-075.84 LATLON	–	41.23255 -75.84457	1,610 ft 491 m	3	–
+41.22_-075.92 LATLON	–	41.21522 -75.91801	3,130 ft 954 m	3	–
+41.22_-075.99 LATLON	–	41.21783 -75.99489	8,900 ft 2,713 m	3	–
+41.46_-078.49 LATLON	–	41.45879 -78.48774	8,900 ft 2,713 m	113	–
+41.65_-080.00 LATLON	–	41.64668 -80.99943	8,900 ft 2,713 m	113	–
+41.78_-083.52 LATLON	–	41.77960 -83.52365	8,900 ft 2,713 m	113	–
+41.88_-087.62 LATLON	–	41.87831 -87.61961	4,840 ft 1,475 m	183	–
+41.87_-087.70 LATLON	–	41.86837 -87.69620	3,130 ft 954 m	3	–
+41.88_-087.77 LATLON	–	41.87854 -87.77274	1,610 ft 491 m	3	–
+41.91_-087.84 LATLON	–	41.90759 -87.84002	520 ft 158 m	3	–
KORD APT	–	41.96312 -87.90240	0 ft 0 m	4	–

KAVP

Region: UNITED STATES
Timezone: AMERICA/NEW_YORK
Runways: 2

Elevation: 962 ft / 293 m
Location: 41.338900 -75.723100
Magnetic Var: 12.021 W

METAR

KAVP 190254Z 26009KT 10SM SCT039 BKN085 01/M07 A2976 RMK AO2 SLP085 T00061067 50005

TAF

KAVP 182341Z 1900/1924 29008G15KT P6SM BKN050 FM191600 26010G16KT P6SM BKN045 FM192200 24009KT P6SM OVC050

Frequencies

TWR - 120.10 MHz - WILKES-BARRE TOWER
APP - 120.95 MHz - WILKES-BARRE APPROACH
REC - 111.60 MHz - ATIS

GND - 121.90 MHz - WILKES-BARRE GROUND
DEP - 120.95 MHz - WILKES-BARRE DEPARTURE
COM - 122.95 MHz - WILKES-BARRE UNICOM

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
04	151 ft 46 m	7,507 ft 2,288 m	32.61 44.63	ASPHALT	0 ft 0 m	194 ft 59 m
22	151 ft 46 m	7,507 ft 2,288 m	212.62 224.64	ASPHALT	0 ft 0 m	374 ft 114 m
10	151 ft 46 m	4,305 ft 1,312 m	91.72 103.75	ASPHALT	0 ft 0 m	207 ft 63 m
28	151 ft 46 m	4,305 ft 1,312 m	271.74 283.76	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04	DME	IAVP	109.90 MHz	18 nm 33 km	- -	-	962 ft 962 m
22	DME	IIZK	109.90 MHz	18 nm 33 km	- -	-	962 ft 962 m
04	LOC-ILS	IAVP	109.90 MHz	18 nm 33 km	32.61 44.63	-	962 ft 962 m
22	LOC-ILS	IIZK	109.90 MHz	18 nm 33 km	212.61 224.63	-	962 ft 962 m
04	GS	IAVP	109.90 MHz	10 nm 19 km	32.61 44.63	3.00	962 ft 962 m
22	GS	IIZK	109.90 MHz	10 nm 19 km	212.61 224.63	3.00	962 ft 962 m

KORD

Region: UNITED STATES
Timezone: AMERICA/CHICAGO
Runways: 6

Elevation: 680 ft / 207 m
Location: 41.973400 -87.906600
Magnetic Var: 4.102 W

METAR

KORD 190251Z 24007KT 10SM FEW250 00/M08 A3005 RMK AO2 SLP184 T00001083 56012

TAF

KORD 190240Z 1903/2006 24011KT P6SM SCT300 FM190600 23012G24KT P6SM BKN100 FM191400 26018G30KT P6SM SCT250 FM1921

Frequencies

REC - 135.40 MHz - ATIS
CLD - 119.25 MHz - CLEARANCE DELIVERY
GND - 118.05 MHz - O'HARE GROUND
GND - 121.75 MHz - O'HARE GROUND
GND - 124.12 MHz - O'HARE GROUND
TWR - 120.75 MHz - O'HARE TOWER
TWR - 126.90 MHz - O'HARE TOWER
TWR - 132.70 MHz - O'HARE TOWER
TWR - 133.00 MHz - O'HARE TOWER
APP - 133.62 MHz - CHICAGO APPROACH
APP - 125.70 MHz - CHICAGO APPROACH
DEP - 125.40 MHz - CHICAGO DEPARTURE
DEP - 128.80 MHz - CHICAGO DEPARTURE
COM - 122.95 MHz - UNICOM
CLD - 121.60 MHz - CLEARANCE DELIVERY
GND - 121.67 MHz - O'HARE GROUND
GND - 121.90 MHz - O'HARE GROUND
GND - 134.12 MHz - O'HARE GROUND
TWR - 121.15 MHz - O'HARE TOWER
TWR - 127.92 MHz - O'HARE TOWER
TWR - 128.15 MHz - O'HARE TOWER
APP - 119.00 MHz - CHICAGO APPROACH
APP - 124.35 MHz - CHICAGO APPROACH
DEP - 125.00 MHz - CHICAGO DEPARTURE
DEP - 127.40 MHz - CHICAGO DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
10C	200 ft 61 m	10,789 ft 3,289 m	89.85 93.95	CONCRETE	0 ft 0 m	397 ft 121 m
28C	200 ft 61 m	10,789 ft 3,289 m	269.88 273.98	CONCRETE	0 ft 0 m	381 ft 116 m
10L	151 ft 46 m	12,996 ft 3,961 m	89.87 93.98	CONCRETE	0 ft 0 m	394 ft 120 m
28R	151 ft 46 m	12,996 ft 3,961 m	269.91 274.01	CONCRETE	0 ft 0 m	285 ft 87 m
04R	151 ft 46 m	8,074 ft 2,461 m	41.40 45.50	CONCRETE	0 ft 0 m	850 ft 259 m
22L	151 ft 46 m	8,074 ft 2,461 m	221.41 225.52	CONCRETE	0 ft 0 m	584 ft 178 m
09R	151 ft 46 m	7,949 ft 2,423 m	89.98 94.08	CONCRETE	0 ft 0 m	148 ft 45 m
27L	151 ft 46 m	7,949 ft 2,423 m	270.00 274.10	CONCRETE	0 ft 0 m	197 ft 60 m
09L	151 ft 46 m	7,484 ft 2,281 m	89.99 94.09	CONCRETE	0 ft 0 m	397 ft 121 m
27R	151 ft 46 m	7,484 ft 2,281 m	270.00 274.11	CONCRETE	0 ft 0 m	397 ft 121 m
10R	151 ft 46 m	7,484 ft 2,281 m	89.85 93.95	CONCRETE	0 ft 0 m	400 ft 122 m
28L	151 ft 46 m	7,484 ft 2,281 m	269.87 273.97	CONCRETE	0 ft 0 m	400 ft 122 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
09L	DME	ISAJ	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
10L	DME	IMED	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
27L	DME	IIAC	110.50 MHz	18 nm 33 km	– –	–	641 ft 641 m
27R	DME	IABU	111.75 MHz	18 nm 33 km	– –	–	668 ft 668 m
28R	DME	ITSL	111.10 MHz	18 nm 33 km	– –	–	678 ft 678 m
04R	LOC-ILS	IFJU	110.10 MHz	18 nm 33 km	41.41 45.51	–	680 ft 680 m
09L	LOC-ILS	ISAJ	111.75 MHz	18 nm 33 km	90.00 94.10	–	680 ft 680 m
09R	LOC-ILS	IJAV	110.50 MHz	18 nm 33 km	89.99 94.09	–	680 ft 680 m
10L	LOC-ILS	IMED	111.10 MHz	18 nm 33 km	89.89 93.99	–	680 ft 680 m
10C	LOC-ILS	ISXH	108.95 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
10R	LOC-ILS	IIZJ	110.75 MHz	18 nm 33 km	89.86 93.96	–	680 ft 680 m
22L	LOC-ILS	ILQQ	110.10 MHz	18 nm 33 km	221.41 225.51	–	680 ft 680 m
27L	LOC-ILS	IIAC	110.50 MHz	18 nm 33 km	269.99 274.09	–	680 ft 680 m
27R	LOC-ILS	IABU	111.75 MHz	18 nm 33 km	270.00 274.10	–	680 ft 680 m
28L	LOC-ILS	IVQX	110.75 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28C	LOC-ILS	IVZE	108.95 MHz	18 nm 33 km	269.87 273.97	–	680 ft 680 m
28R	LOC-ILS	ITSL	111.10 MHz	18 nm 33 km	269.88 273.98	–	680 ft 680 m
04R	GS	IFJU	110.10 MHz	10 nm 19 km	41.41 45.51	3.00	680 ft 680 m
09L	GS	ISAJ	111.75 MHz	10 nm 19 km	90.00 94.10	3.00	680 ft 680 m
09R	GS	IJAV	110.50 MHz	10 nm 19 km	89.99 94.09	3.00	680 ft 680 m
10L	GS	IMED	111.10 MHz	10 nm 19 km	89.89 93.99	3.00	680 ft 680 m
10C	GS	ISXH	108.95 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
10R	GS	IIZJ	110.75 MHz	10 nm 19 km	89.86 93.96	3.00	680 ft 680 m
22L	GS	ILQQ	110.10 MHz	10 nm 19 km	221.41 225.51	3.00	680 ft 680 m
27L	GS	IIAC	110.50 MHz	10 nm 19 km	269.99 274.09	3.00	680 ft 680 m
27R	GS	IABU	111.75 MHz	10 nm 19 km	270.00 274.10	3.00	680 ft 680 m
28L	GS	IVQX	110.75 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28C	GS	IVZE	108.95 MHz	10 nm 19 km	269.87 273.97	3.00	680 ft 680 m
28R	GS	ITSL	111.10 MHz	10 nm 19 km	269.88 273.98	3.00	680 ft 680 m