

# KJFK

John F Kennedy Intl


# KIAD

Washington Dulles Intl

2024/05/13 0249Z

KJFK EKSEW KIAD

198.13 nm / 366.93 km



## Notes

Basic altitude profile:

- Ascent Rate: 3000ft/min
- Ascent Speed: 240kts
- Cruise Altitude: 26000ft
- Cruise Speed: 330kts
- Descent Rate: 1600ft/min
- Descent Speed: 245kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes



## Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KJFK	-	40.63990	0 ft	-	John F Kennedy Intl
APT	-	-73.77666	0 m		
EKSEW	-	39.82961	22,800 ft	91	-
FIX	-	-75.47248	6,949 m		
KIAD	-	38.94771	0 ft	106	Washington Dulles Intl
APT	-	-77.46086	0 m		

## KJFK

Region: UNITED STATES  
Timezone: AMERICA/NEW\_YORK  
Runways: 4

Elevation: 12 ft / 4 m  
Location: 40.640100 -73.776500  
Magnetic Var: 12.819 W

## METAR

KJFK 130151Z 23010KT 10SM FEW040 FEW090 SCT190 BKN250 10/06 A3001 RMK A02 SLP162 T01000056

## TAF

TAF AMD KJFK 130231Z 1303/1406 23007KT P6SM FEW040 SCT250 FM131400 21009KT P6SM SCT250 FM131700 18015KT P6SM SCT10

## Frequencies

REC - 115.40 MHz - D-ATIS	REC - 117.70 MHz - D-ATIS
REC - 128.72 MHz - D-ATIS	COM - 122.95 MHz - UNICOM
CLD - 135.05 MHz - CLEARANCE DELIVERY	GND - 121.90 MHz - KENNEDY GROUND
GND - 121.65 MHz - KENNEDY GROUND	TWR - 119.10 MHz - KENNEDY TOWER
TWR - 123.90 MHz - KENNEDY TOWER	APP - 125.70 MHz - NEW YORK APPROACH
APP - 128.12 MHz - NEW YORK APPROACH	APP - 118.40 MHz - NEW YORK APPROACH
APP - 123.70 MHz - NEW YORK APPROACH	APP - 126.80 MHz - NEW YORK APPROACH
APP - 132.40 MHz - NEW YORK APPROACH	APP - 134.35 MHz - NEW YORK APPROACH
DEP - 135.90 MHz - NEW YORK DEPARTURE	DEP - 123.70 MHz - NEW YORK DEPARTURE
DEP - 124.75 MHz - NEW YORK DEPARTURE	DEP - 134.35 MHz - NEW YORK DEPARTURE

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
13R	200 ft	14,526 ft	120.83	CONCRETE	2,057 ft	390 ft
	61 m	4,428 m	133.65		627 m	119 m
31L	200 ft	14,526 ft	300.86	CONCRETE	3,271 ft	495 ft
	61 m	4,428 m	313.68		997 m	151 m
13L	151 ft	10,010 ft	120.85	CONCRETE	912 ft	387 ft
	46 m	3,051 m	133.67		278 m	118 m
31R	151 ft	10,010 ft	300.87	CONCRETE	1,037 ft	177 ft
	46 m	3,051 m	313.69		316 m	54 m
04R	200 ft	8,407 ft	30.67	ASPHALT	0 ft	440 ft
	61 m	2,562 m	43.49		0 m	134 m
22L	200 ft	8,407 ft	210.68	ASPHALT	0 ft	505 ft
	61 m	2,562 m	223.50		0 m	154 m
04L	200 ft	12,091 ft	30.67	CONCRETE	459 ft	200 ft
	61 m	3,685 m	43.49		140 m	61 m
22R	200 ft	12,091 ft	210.68	CONCRETE	3,425 ft	407 ft
	61 m	3,685 m	223.50		1,044 m	124 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
04L	DME	IHIQ	110.90 MHz	18 nm	-	-	13 ft
				33 km	-		13 m
04R	DME	IJFK	109.50 MHz	18 nm	-	-	13 ft
				33 km	-		13 m
13L	DME	ITLK	111.50 MHz	18 nm	-	-	13 ft
				33 km	-		13 m
22L	DME	IIWY	110.90 MHz	18 nm	-	-	13 ft
				33 km	-		13 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
22R	DME	IJOC	109.50 MHz	18 nm	-	-	13 ft
				33 km	-		13 m
31R	DME	IRTH	111.50 MHz	18 nm	-	-	13 ft
				33 km	-		13 m
04L	LOC-ILS	IHIQ	110.90 MHz	18 nm	30.68	-	12 ft
				33 km	43.50		12 m
04R	LOC-ILS	IJFK	109.50 MHz	18 nm	30.67	-	12 ft
				33 km	43.49		12 m
13L	LOC-ILS	ITLK	111.50 MHz	18 nm	120.87	-	12 ft
				33 km	133.69		12 m
22L	LOC-ILS	IIWY	110.90 MHz	18 nm	210.67	-	12 ft
				33 km	223.49		12 m
22R	LOC-ILS	IJOC	109.50 MHz	18 nm	210.68	-	12 ft
				33 km	223.50		12 m
31L	LOC-ILS	IMOH	111.35 MHz	18 nm	300.84	-	12 ft
				33 km	313.66		12 m
31R	LOC-ILS	IRTH	111.50 MHz	18 nm	300.87	-	12 ft
				33 km	313.69		12 m
04L	GS	IHIQ	110.90 MHz	10 nm	30.68	3.00	12 ft
				19 km	43.50		12 m
04R	GS	IJFK	109.50 MHz	10 nm	30.67	3.00	12 ft
				19 km	43.49		12 m
13L	GS	ITLK	111.50 MHz	10 nm	120.87	3.00	12 ft
				19 km	133.69		12 m
22L	GS	IIWY	110.90 MHz	10 nm	210.67	3.00	12 ft
				19 km	223.49		12 m
22R	GS	IJOC	109.50 MHz	10 nm	210.68	3.00	12 ft
				19 km	223.50		12 m
31L	GS	IMOH	111.35 MHz	10 nm	300.84	3.00	12 ft
				19 km	313.66		12 m
31R	GS	IRTH	111.50 MHz	10 nm	300.87	3.00	12 ft
				19 km	313.69		12 m

## KIAD

Region: UNITED STATES  
Timezone: AMERICA/NEW\_YORK  
Runways: 4

Elevation: 312 ft / 95 m  
Location: 38.947700 -77.460900  
Magnetic Var: 10.664 W

## METAR

KIAD 130152Z VRB05KT 10SM FEW080 12/07 A2998 RMK AO2 SLP151 T01220072 \$

## TAF

TAF KIAD 122340Z 1300/1406 35007KT P6SM FEW050 BKN070 FM130400 00000KT P6SM FEW070 FM131200 19008KT P6SM FEW040 FM131800 23010KT P6SM FEW040

## Frequencies

COM - 122.95 MHz - UNICOM	REC - 134.85 MHz - D-ATIS
CLD - 135.70 MHz - CLEARANCE DELIVERY	GND - 121.62 MHz - DULLES GROUND
GND - 121.90 MHz - DULLES GROUND	TWR - 120.10 MHz - DULLES TOWER
TWR - 120.25 MHz - DULLES TOWER	TWR - 134.42 MHz - DULLES TOWER
APP - 120.45 MHz - POTOMAC APPROACH	APP - 126.10 MHz - POTOMAC APPROACH
APP - 128.52 MHz - POTOMAC APPROACH	DEP - 126.65 MHz - POTOMAC DEPARTURE
DEP - 125.05 MHz - POTOMAC DEPARTURE	

## Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
01L	151 ft	9,408 ft	0.64	CONCRETE	0 ft	404 ft
	46 m	2,868 m	11.30		0 m	123 m
19R	151 ft	9,408 ft	180.64	CONCRETE	0 ft	404 ft
	46 m	2,868 m	191.30		0 m	123 m
01C	151 ft	11,510 ft	0.65	CONCRETE	0 ft	407 ft
	46 m	3,508 m	11.31		0 m	124 m
19C	151 ft	11,510 ft	180.65	CONCRETE	0 ft	43 ft
	46 m	3,508 m	191.31		0 m	13 m
01R	151 ft	11,510 ft	0.66	CONCRETE	0 ft	43 ft
	46 m	3,508 m	11.33		0 m	13 m
19L	151 ft	11,510 ft	180.66	CONCRETE	0 ft	387 ft
	46 m	3,508 m	191.33		0 m	118 m
12	151 ft	10,513 ft	110.71	CONCRETE	0 ft	20 ft
	46 m	3,204 m	121.37		0 m	6 m
30	151 ft	10,513 ft	290.73	CONCRETE	0 ft	387 ft
	46 m	3,204 m	301.39		0 m	118 m

## Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
01R	DME	IIAD	110.10 MHz	18 nm	-	-	314 ft
				33 km	-		314 m
19L	DME	ISGC	110.10 MHz	18 nm	-	-	314 ft
				33 km	-		314 m
19R	DME	IISU	110.75 MHz	18 nm	-	-	313 ft
				33 km	-		313 m
01C	LOC-ILS	IOSZ	111.30 MHz	18 nm	0.65	-	312 ft
				33 km	11.31		312 m
01R	LOC-ILS	IIAD	110.10 MHz	18 nm	0.67	-	312 ft
				33 km	11.33		312 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
12	LOC-ILS	IAJU	109.30 MHz	18 nm	110.74	-	312 ft
				33 km	121.40		312 m
19C	LOC-ILS	IDLX	111.30 MHz	18 nm	180.65	-	312 ft
				33 km	191.31		312 m
19L	LOC-ILS	ISGC	110.10 MHz	18 nm	180.67	-	312 ft
				33 km	191.33		312 m
19R	LOC-ILS	IISU	110.75 MHz	18 nm	180.58	-	312 ft
				33 km	191.24		312 m
01L	LOC-ILS	IOIU	110.75 MHz	18 nm	0.58	-	312 ft
				33 km	11.24		312 m
01C	GS	IOSZ	111.30 MHz	10 nm	0.65	3.00	312 ft
				19 km	11.31		312 m
01R	GS	IIAD	110.10 MHz	10 nm	0.67	3.00	312 ft
				19 km	11.33		312 m
12	GS	IAJU	109.30 MHz	10 nm	110.74	3.00	312 ft
				19 km	121.40		312 m
19C	GS	IDLX	111.30 MHz	10 nm	180.65	3.00	312 ft
				19 km	191.31		312 m
19L	GS	ISGC	110.10 MHz	10 nm	180.67	3.00	312 ft
				19 km	191.33		312 m
19R	GS	IISU	110.75 MHz	10 nm	180.58	3.00	312 ft
				19 km	191.24		312 m
01L	GS	IOIU	110.75 MHz	10 nm	0.58	3.00	312 ft
				19 km	11.24		312 m