



Notes

Basic altitude profile:

- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:

- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
KLVK	-	37.69318	0 ft	-	Livermore Muni
APT	-	-121.82037	0 m		
GALTS	-	38.27056	15,200 ft	42	-
FIX	-	-121.29354	4,633 m		
KRTS	-	39.66780	0 ft	106	Reno Stead
APT	-	-119.87662	0 m		

KLVK

Region: UNITED STATES
Timezone: AMERICA/LOS_ANGELES
Runways: 2

Elevation: 399 ft / 122 m
Location: 37.693200 -121.820000
Magnetic Var: 12.771 E

METAR

KLVK 102053Z VRB03KT 10SM CLR 29/08 A2990 RMK A02 SLP122 T02890078 58016

TAF

TAF KLVK 101747Z 1018/1118 30005KT P6SM SKC FM102000 29011KT P6SM SKC FM110500 25006KT P6SM SKC

Frequencies

REC - 119.65 MHz - ATIS
COM - 122.95 MHz - UNICOM
TWR - 118.10 MHz -
APP - 125.35 MHz - NORCAL APP/DEP
COM - 118.10 MHz - CTAF
GND - 121.60 MHz -
APP - 123.85 MHz - NORCAL APP/DEP

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07L	98 ft	5,241 ft	90.57	ASPHALT	0 ft	151 ft
	30 m	1,598 m	77.80		0 m	46 m
25R	98 ft	5,241 ft	270.58	ASPHALT	0 ft	151 ft
	30 m	1,598 m	257.81		0 m	46 m
07R	75 ft	2,694 ft	90.58	ASPHALT	0 ft	0 ft
	23 m	821 m	77.81		0 m	0 m
25L	75 ft	2,694 ft	270.58	ASPHALT	0 ft	0 ft
	23 m	821 m	257.81		0 m	0 m

Approach Nav aids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
25R	LOC-ILS	ILVK	110.50 MHz	18 nm	270.56	-	365 ft
				33 km	257.79		365 m
25R	GS	ILVK	110.50 MHz	10 nm	271.15	3.00	393 ft
				19 km	258.38		393 m