LIRF

Roma Fiumicino Leonardo Da Vinci


LFPG

Paris Charles De Gaulle

2024/03/29 0446Z

LIRF ELB **UL50** BANKO **A1** SPR **UH10** DJL **UH37** TUNOR LFPG

600.04 nm / 1111.27 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 37000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LIRF APT	- -	41.81081 12.25090	0 ft 0 m	-	Roma Fiumicino Leonardo Da Vinci
ELB VOR	- -	42.73069 10.39572	34,000 ft 10,363 m	99	ELBA VORTAC
MAURO FIX	UL50 AWY-HI	43.18806 9.88750	34,000 ft 10,363 m	35	-
KONER FIX	UL50 AWY-HI	43.50472 9.53000	34,000 ft 10,363 m	24	-
KAFEE FIX	UL50 AWY-HI	43.80000 9.19194	34,000 ft 10,363 m	23	-
UNITA FIX	UL50 AWY-HI	43.94444 9.02500	34,000 ft 10,363 m	11	-
IXITO FIX	UL50 AWY-HI	44.13472 8.80361	34,000 ft 10,363 m	14	-
ANAKI FIX	UL50 AWY-HI	44.20111 8.72556	34,000 ft 10,363 m	5	-
LAGEN FIX	UL50 AWY-HI	44.39417 8.49806	34,000 ft 10,363 m	15	-
NEDED FIX	UL50 AWY-HI	44.69389 8.14056	34,000 ft 10,363 m	23	-
TOP VOR	UL50 AWY-HI	44.92525 7.86166	34,000 ft 10,363 m	18	TORINO VOR-DME
KERES FIX	UL50 AWY-HI	45.22139 7.59778	34,000 ft 10,363 m	21	-
ADISO FIX	UL50 AWY-HI	45.55917 7.29333	34,000 ft 10,363 m	24	-
BANKO FIX	UL50 AWY-HI	45.82000 7.05500	34,000 ft 10,363 m	18	-
SPR29 FIX	A1 AWY-LO	46.06361 6.82806	18,500 ft 5,639 m	17	-
SPR20 FIX	A1 AWY-LO	46.18944 6.71083	18,500 ft 5,639 m	8	-
SPR15 FIX	A1 AWY-LO	46.27218 6.62959	18,500 ft 5,639 m	6	-
SPR VOR	A1 AWY-LO	46.46869 6.44806	18,500 ft 5,639 m	13	ST. PREX VOR-DME
SPR14 FIX	UH10 AWY-HI	46.62222 6.19167	34,000 ft 10,363 m	14	-
SIROD FIX	UH10 AWY-HI	46.72694 6.01944	34,000 ft 10,363 m	9	-
DJL VOR	UH10 AWY-HI	47.27078 5.09733	30,200 ft 9,205 m	49	DIJON-LONGVIC VOR-DME
TUNOR FIX	UH37 AWY-HI	47.88333 4.14111	18,700 ft 5,700 m	53	-
LFPG APT	- -	49.00974 2.56262	0 ft 0 m	92	Paris Charles De Gaulle

LIRF

Region: ITALY
Timezone: EUROPE/ROME
Runways: 3

Elevation: 13 ft / 4 m
Location: 41.810800 12.250900
Magnetic Var: 3.653 E

METAR

LIRF 290420Z 14012KT CAVOK 15/12 Q1015 NOSIG

TAF

TAF LIRF 282300Z 2900/3006 14014KT 9000 NSC TEMPO 2900/2908 14015G25KT BECMG 2908/2910 14020G32KT BECMG 2918/2920

Frequencies

REC - 120.17 MHz - ATIS ARRIVAL
REC - 121.85 MHz - ATIS DEPARTURE
GND - 121.72 MHz - FIUME APRON
GND - 121.90 MHz - FIUME GROUND
TWR - 127.62 MHz - FIUME TOWER
TWR - 118.70 MHz - FIUME TOWER
DEP - 131.10 MHz - ROMA DEPARTURE
APP - 125.50 MHz - ROMA ARRIVAL
APP - 131.25 MHz - ROMA DIRECT

REC - 126.12 MHz - ATIS ARRIVAL
CLD - 121.80 MHz - CLEARANCE DELIVERY
GND - 121.67 MHz - FIUME GROUND
GND - 122.12 MHz - FIUME GROUND
TWR - 123.72 MHz - FIUME TOWER
DEP - 130.90 MHz - ROMA DEPARTURE
APP - 127.95 MHz - ROMA ARRIVAL
APP - 119.20 MHz - ROMA DIRECT

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
07	148 ft 45 m	10,859 ft 3,310 m	69.68 66.03	ASPHALT	1,348 ft 411 m	0 ft 0 m
25	148 ft 45 m	10,859 ft 3,310 m	249.71 246.05	ASPHALT	0 ft 0 m	0 ft 0 m
16R	197 ft 60 m	12,814 ft 3,906 m	162.66 159.01	ASPHALT	0 ft 0 m	0 ft 0 m
34L	197 ft 60 m	12,814 ft 3,906 m	342.67 339.02	ASPHALT	0 ft 0 m	0 ft 0 m
16L	197 ft 60 m	12,814 ft 3,906 m	162.68 159.03	ASPHALT	0 ft 0 m	0 ft 0 m
34R	197 ft 60 m	12,814 ft 3,906 m	342.69 339.04	ASPHALT	0 ft 0 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
25	DME	FEE	110.15 MHz	25 nm 46 km	- -	-	25 ft 25 m
34L	DME	ISW	108.90 MHz	25 nm 46 km	- -	-	15 ft 15 m
34R	DME	FSS	111.55 MHz	25 nm 46 km	- -	-	15 ft 15 m
16L	LOC-ILS	IFLL	108.10 MHz	18 nm 33 km	162.69 159.04	-	13 ft 13 m
16R	LOC-ILS	IFRR	109.75 MHz	18 nm 33 km	162.67 159.02	-	13 ft 13 m
25	LOC-ILS	FEE	110.15 MHz	18 nm 33 km	249.69 246.04	-	13 ft 13 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
34L	LOC-ILS	IFSW	108.90 MHz	18 nm 33 km	342.67 339.02	-	13 ft 13 m
34R	LOC-ILS	FSS	111.55 MHz	18 nm 33 km	342.69 339.04	-	13 ft 13 m
16L	GS	IFLL	108.10 MHz	10 nm 19 km	162.69 159.04	3.00	13 ft 13 m
16R	GS	IFRR	109.75 MHz	10 nm 19 km	162.67 159.02	3.00	13 ft 13 m
25	GS	FEE	110.15 MHz	10 nm 19 km	249.69 246.04	3.00	13 ft 13 m
34L	GS	IFSW	108.90 MHz	10 nm 19 km	342.67 339.02	3.00	13 ft 13 m
34R	GS	FSS	111.55 MHz	10 nm 19 km	342.69 339.04	3.00	13 ft 13 m

LFPG

Region: FRANCE
Timezone: EUROPE/PARIS
Runways: 4

Elevation: 392 ft / 119 m
Location: 49.009700 2.562570
Magnetic Var: 1.480 E

METAR

LFPG 290430Z 22013KT 9999 BKN016 10/07 Q0991 NOSIG

TAF

TAF LFPG 282300Z 2900/3006 16010KT CAVOK TX14/2915Z TN07/2905Z TEMPO 2900/2904 4000 RA BKN040 PROB40 TEMPO 2905/2

Frequencies

REC - 128.32 MHz - ATIS
TWR - 120.90 MHz - DE GAULLE TOWER
TWR - 119.62 MHz - DE GAULLE TOWER
TWR - 118.65 MHz - DE GAULLE TOWER
TWR - 120.65 MHz - DE GAULLE TOWER
GND - 125.30 MHz - DE GAULLE GROUND
CLD - 121.80 MHz - CLEARANCE DELIVERY
APP - 119.85 MHz - DE GAULLE APPROACH
APP - 125.82 MHz - DE GAULLE APPROACH
DEP - 124.35 MHz - DE GAULLE DEPARTURE
DEP - 131.20 MHz - DE GAULLE DEPARTURE

REC - 127.12 MHz - ATIS
TWR - 125.32 MHz - DE GAULLE TOWER
TWR - 119.25 MHz - DE GAULLE TOWER
TWR - 123.60 MHz - DE GAULLE TOWER
GND - 121.90 MHz - DE GAULLE GROUND
GND - 121.70 MHz - DE GAULLE GROUND
APP - 118.15 MHz - DE GAULLE APPROACH
APP - 121.15 MHz - DE GAULLE APPROACH
APP - 126.42 MHz - DE GAULLE APPROACH
DEP - 126.57 MHz - DE GAULLE DEPARTURE
DEP - 133.37 MHz - DE GAULLE DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
08L	148 ft 45 m	13,713 ft 4,180 m	85.31 83.83	ASPHALT	0 ft 0 m	489 ft 149 m
26R	148 ft 45 m	13,713 ft 4,180 m	265.35 263.87	ASPHALT	1,877 ft 572 m	279 ft 85 m
09L	197 ft 60 m	8,866 ft 2,703 m	85.32 83.84	ASPHALT	0 ft 0 m	0 ft 0 m
27R	197 ft 60 m	8,866 ft 2,703 m	265.35 263.87	ASPHALT	0 ft 0 m	0 ft 0 m
08R	197 ft 60 m	8,833 ft 2,692 m	85.33 83.85	ASPHALT	0 ft 0 m	489 ft 149 m
26L	197 ft 60 m	8,833 ft 2,692 m	265.35 263.87	ASPHALT	0 ft 0 m	486 ft 148 m
09R	148 ft 45 m	13,746 ft 4,190 m	85.30 83.82	ASPHALT	0 ft 0 m	0 ft 0 m
27L	148 ft 45 m	13,746 ft 4,190 m	265.34 263.86	ASPHALT	1,959 ft 597 m	0 ft 0 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
08R	DME	DSE	108.55 MHz	18 nm 33 km	- -	-	358 ft 358 m
09L	DME	PNE	109.35 MHz	18 nm 33 km	- -	-	392 ft 392 m
09R	DME	CGE	110.10 MHz	18 nm 33 km	- -	-	392 ft 392 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
26L	DME	DSU	108.35 MHz	18 nm	– –	–	338 ft 338 m
27L	DME	CGW	110.70 MHz	18 nm 33 km	– –	–	407 ft 407 m
27R	DME	PNW	110.35 MHz	18 nm 33 km	– –	–	392 ft 392 m
08L	LOC-ILS	GLE	108.70 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
08R	LOC-ILS	DSE	108.55 MHz	18 nm 33 km	85.34 83.86	–	392 ft 392 m
09L	LOC-ILS	PNE	109.35 MHz	18 nm 33 km	85.33 83.85	–	392 ft 392 m
09R	LOC-ILS	CGE	110.10 MHz	18 nm 33 km	85.32 83.84	–	392 ft 392 m
26L	LOC-ILS	DSU	108.35 MHz	18 nm 33 km	265.34 263.86	–	392 ft 392 m
26R	LOC-ILS	GAU	111.95 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
27L	LOC-ILS	CGW	110.70 MHz	18 nm 33 km	265.32 263.84	–	392 ft 392 m
27R	LOC-ILS	PNW	110.35 MHz	18 nm 33 km	265.33 263.85	–	392 ft 392 m
08L	GS	GLE	108.70 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
08R	GS	DSE	108.55 MHz	10 nm 19 km	85.34 83.86	3.00	392 ft 392 m
09L	GS	PNE	109.35 MHz	10 nm 19 km	85.33 83.85	3.00	392 ft 392 m
09R	GS	CGE	110.10 MHz	10 nm 19 km	85.32 83.84	3.00	392 ft 392 m
26L	GS	DSU	108.35 MHz	10 nm 19 km	265.34 263.86	3.00	392 ft 392 m
26R	GS	GAU	111.95 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m
27L	GS	CGW	110.70 MHz	10 nm 19 km	265.32 263.84	3.00	392 ft 392 m
27R	GS	PNW	110.35 MHz	10 nm 19 km	265.33 263.85	3.00	392 ft 392 m