LGAV

Athens Intl Airport Elefterios Venizel


LGHI

Chios

2024/03/19 0352Z

LGAV KRO LGHI

106.77 nm / 197.74 km



Notes

Basic altitude profile:
- Ascent Rate: 2500ft/min
- Ascent Speed: 250kts
- Cruise Altitude: 35000ft
- Cruise Speed: 420kts
- Descent Rate: 1500ft/min
- Descent Speed: 250kts

Options:
- Use NATs: yes
- Use PACOTS: yes
- Use low airways: yes
- Use high airways: yes

Route

Ident Type	Via	Lat Lon	Alt	Dist (nm)	Name
LGAV APT	–	37.93636 23.94447	0 ft 0 m	–	Athens Intl Airport Elefterios Venizel
KRO VOR	–	37.99414 24.49492	9,300 ft 2,835 m	26	KARISTOS VOR-DME
LGHI APT	–	38.34318 26.14058	0 ft 0 m	80	Chios

LGAV

Region: GREECE
Timezone: EUROPE/ATHENS
Runways: 2

Elevation: 308 ft / 94 m
Location: 37.936700 23.944500
Magnetic Var: 5.093 E

METAR

LGAV 190320Z VRB01KT 9999 FEW030 08/07 Q1011 NOSIG

TAF

TAF TAF LGAV 182300Z 1900/1924 VRB05KT 9999 FEW030 SCT070 BECMG 1905/1907 SCT025 BKN070 PROB40 TEMPO 1912/1924 50

Frequencies

REC - 136.12 MHz - ATIS
REC - 124.02 MHz - ATHENS INFORMATION
TWR - 122.10 MHz - VENIZELOS TOWER
GND - 121.75 MHz - VENIZELOS GROUND
GND - 121.90 MHz - VENIZELOS GROUND
CLD - 118.67 MHz - CLEARANCE DELIVERY
APP - 130.25 MHz - ATHENS APPROACH
APP - 126.57 MHz - ATHENS APPROACH
APP - 121.40 MHz - ATHENS APPROACH
APP - 118.47 MHz - ATHENS DIRECT
DEP - 128.95 MHz - ATHENS DEPARTURE
REC - 131.17 MHz - ATHENS INFORMATION
TWR - 136.27 MHz - VENIZELOS TOWER
TWR - 118.62 MHz - VENIZELOS TOWER
GND - 121.95 MHz - VENIZELOS GROUND
GND - 121.80 MHz - VENIZELOS GROUND
APP - 132.97 MHz - ATHENS APPROACH
APP - 128.95 MHz - ATHENS APPROACH
APP - 125.52 MHz - ATHENS APPROACH
APP - 121.40 MHz - ATHENS DIRECT
DEP - 118.30 MHz - ATHENS DEPARTURE

Runways

Ident	Width	Length	Bearing (true) (mag)	Surface	Threshold Offset	Overrun Length
03R	151 ft 46 m	13,135 ft 4,004 m	36.87 31.78	ASPHALT	984 ft 300 m	394 ft 120 m
21L	151 ft 46 m	13,135 ft 4,004 m	216.89 211.80	ASPHALT	984 ft 300 m	394 ft 120 m
03L	151 ft 46 m	12,478 ft 3,803 m	36.86 31.76	ASPHALT	984 ft 300 m	394 ft 120 m
21R	151 ft 46 m	12,478 ft 3,803 m	216.87 211.78	ASPHALT	984 ft 300 m	394 ft 120 m

Approach Navaids

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03L	DME	IATL	110.50 MHz	18 nm 33 km	- -	-	255 ft 255 m
21L	DME	IEVL	111.10 MHz	18 nm 33 km	- -	-	303 ft 303 m
21R	DME	IEVR	110.50 MHz	18 nm 33 km	- -	-	282 ft 282 m
03L	LOC-ILS	IATL	110.50 MHz	18 nm 33 km	36.52 31.43	-	282 ft 282 m
03R	LOC-ILS	IATR	111.10 MHz	18 nm 33 km	36.97 31.88	-	302 ft 302 m
21L	LOC-ILS	IEVL	111.10 MHz	18 nm 33 km	216.52 211.43	-	271 ft 271 m
21R	LOC-ILS	IEVR	110.50 MHz	18 nm 33 km	216.50 211.41	-	255 ft 255 m

Runway	Type	Ident	Frequency	Range	Bearing (true) (mag)	Slope	Elevation
03L	GS	IATL	110.50 MHz	10 nm	37.04	3.00	255 ft
				19 km	31.94		255 m
03R	GS	IATR	111.10 MHz	10 nm	37.07	3.00	271 ft
				19 km	31.97		271 m
21L	GS	IEVL	111.10 MHz	10 nm	217.07	3.00	302 ft
				19 km	211.97		302 m
21R	GS	IEVR	110.50 MHz	10 nm	217.04	3.00	282 ft
				19 km	211.94		282 m